

Taking the soft top down

1. Remove back window
 - a. Unzip the zipper starting from the lower right hand side up and over to the left until it unhooks, place in location that will not scratch the window
2. Remove side windows
 - a. Open the rear door closest to the window you are removing
 - b. Lift the Velcro on the rear of the window and unzip the entire zipper
 - c. Starting from the rear lower portion of the window pull the window down and towards you so that the bottom ridge separates from the vehicle, then pull out of the window frame slot and completely off.
 - d. Store window where it will not be scratched
 - e. Repeat for window on the other side
3. Unhook the top
 - a. Unhook the sun visors in the front of your vehicle and move them to the side to fully expose your top latches
 - b. Locate the latches in the front of the vehicle that are located behind your sun visor and unlatch both the driver side and passenger side latch
 - c. Move to the rear of the vehicle where you will find the rear flap that connects the top to the Jeep on either side of the rear window
 - d. On one side of the material where it meets the steel lip on the Jeep, pull down and pull out to separate the material from the Jeep
 - e. Swing the material up and over the roof so that each side when removed meets in the middle at the rear of the soft top
4. Bring the top down (ask a friend to help for this portion to make it easier)
 - a. Starting at the front of the Jeep pull the top back so that it folds back exposing the front half of the jeep
 - b. There is a latch on either side of the Jeep at the top about mid-way, pressing that latch will release the top bar and allow you to bring the top back the rest of the way
 - c. As the top comes towards the back you want to manipulate the folds of the soft top material so that it pulls out to the rear and folds nicely, you may need to play with it a little once it is completely down in order for the folded top to sit as low as possible

You're done, unless of course you are motivated enough to remove the doors too!

Putting the soft top back up

1. Bringing the top back up
 - a. Unhook the sun visor and move it to the side to fully expose the area you will be required to re-latch the soft top
 - b. Grab a friend to assist you with the next step (possible by yourself but much more difficult)
 - c. Grab the soft top poles where they come to a full bend (where the poles fold completely) and with those facing the sky lift them over the first half of the Jeep
 - d. When the top lowers onto the plastic window sills, make sure that the plastic piece in the soft top aligns with the plastic slot on the top of the window sill
 - e. When you slide the top forward over those slots the round piece on the inside should lock into the latch that was used to originally release the center of the top
 - f. Once those are latched in, grab the top that is folded back and bring it forward so that it meets with the top of the windshield

- g. Sit in the driver or passenger seat to latch the hooks on the front of the soft top to the hooks on the Jeep which are located behind the visors but do not clamp them fully, just latch them so that they catch onto the hook loosely
 - h. Head to the back of the Jeep towards the rear panels on either side of the rear window, in order to attach these to the Jeep you need to face the plastic pieces on the bottom on an angle downward into the small lip near the top of the steel body
 - i. By pushing down on the material it will cause the plastic tabs to lock in underneath the steel lip
 - j. Once both rear side panels are installed as described above, move back up to the front seat and lock in those latches behind the visor fully and replace the sun visor in its original position
2. Install side windows
- a. Start by opening the rear door on the side you are installing
 - b. Attach the zipper and zip it only 2-3 inches
 - c. On the plastic window well there is a slot that the hard plastic line of the window fits into so that it does not flap in the wind and it keeps the water out, in order to insert the window edge into this slot you need to grab the bottom edge of the material closest to the door and pull downwards and toward the front of the vehicle in order to slide it into that slot
 - d. Once the window is fitted into the slot you can zip the rest of the zipper
 - e. Once zipped, you need to attached the bottom lip; similar to the rear panels the side windows have a plastic lip sewed into the bottom which you need to angle downward below the lip
 - f. Start by pushing down on the side closest to the door and work your way slowly back to ensure the window tucks under the lip all the way
 - g. The last step is to push the material at the top under the top flap so that the Velcro adheres
 - h. Repeat with opposite side window
3. Install rear window
- a. The rear window consists of a soft portion and a solid bar that slides onto the bottom of the window, this bar is what created a solid weather seal
 - b. Since the bar makes the bottom of the window stiff, slide the bar about 3-4 inches to the right in order to make a small portion on the left hand side more flexible; you will require that flexibility in order to push the material into the side where the zipper is located on the left hand side and zip it up
 - c. Before zipping the rest of the window move the bar back in line with the center
 - d. Once you zip the window up you will notice that both sides will have a zipper, if you want to access the truck to place something large inside you can partially zip up both sides and swing the window over the top but in order to take the window back out the zippers will always have to be on the left
 - e. Once the window is in you need to use your wrist to roll the bottom bar into the plastic guides on either side, if the bar is not installed properly you will notice that the bar will not seal properly when the tailgate is closed.
 - f. Done!